THE ULTIMATE GAP **REMEDIATION SYSTEM FOR FIRE DOORS**

WHAT IS FRAMEFIT?

FrameFit is a NEW & UNIQUE fully tested product that fits directly to door frames to reduce gap sizes to meet current fire door regulations.

Fire Door Inspectors will report a fire door as 'Non-Compliant' with gaps of over 4mm between the frame and leaf. On the bottom of a fire door, gaps of over 8mm (Fire Only Door) and gaps of over 3mm (Fire & Smoke Doors) will also be reported as 'Non-Compliant.' Until now the only remedy for excessive gaps is to replace the door with a new one.

FrameFit is designed with ease of fitting in mind, with selective thickness's such 1.5 mm (with or without smoke seal) - 3 mm and 5 mm to suit any gap variation. Widths to suit FD30's 44mm and FD60's 54mm. FrameFit comes on a roll and is easily cut to size and applied with minimal tools required.





Fully tested to BS 476 Part 22 & BS EN 1634-1

77%

Of inspected fire doors failed due to gaps between the door and frame.

- FDIS Report, 2021



www.performanceadhesives.co.uk 🔌 01442 899960 📡 info@p-a-l.co.uk











KEY FEATURES & BENEFITS

- Tested to all core types.
- Brings non-compliant fire doors back into compliance.
- Ease and speed of installation to extend the life of existing fire doors.
- Avoids cost of replacing a door.
- Helps to keep trees in the ground.
- Made with recycled plastics.

FIRE DOOR LEGISLATION

For information on incoming legislation for buildings above 11M [The Fire Safety (England) Regulations 2022], visit:

https://bit.ly/3B9SzIS

For information on current legislation for buildings below 11M [The Fire Safety Act 2021], visit:

https://bit.ly/3cDwmAb





01442 899960



info@p-a-l.co.uk

