

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Smart Protecti

Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Nullifire SC902 B
- · MSDS code: W-N-SC902B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@cpg-europe.com

· Further information obtainable from:

See above-mentioned address

Tremco CPG UK Ltd Coupland Road, Hindley Green, Wigan, WN2 4HT T: +44 (0) 1942251400, F: +44 (0) 1942251410 www.cpg-europe.com, info.uk@cpg-europe.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

- · Additional information: (EC) 1272/2008 'CLP' & GB-CLP: 2.6.4.5 (Flam. Liq. 3)
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 1)

· Signal word Danger

· Contains:

3-(trimethoxysilyl)propylamine

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

VOC 2004/42/CE & UK SI 2012/1715 (A / j) = <500 g/l

Nullifire SC902 B

= 112 g/l

• 2.3 Other hazards No further relevant information available.

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	5-<10%
CAS: 13822-56-5 EINECS: 237-511-5 Reg.nr.: 01-2119510159-45-xxxx	3-(trimethoxysilyl)propylamine Eye Dam. 1, H318; Skin Irrit. 2, H315	5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	1-<5%

· SVHC -

Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Methanol (CAS 67-56-1)



Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Take affected persons out of danger area and lay down.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

Irritant to skin and mucous membranes.

Risk of serious damage to eyes.

- · **Hazards** No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Smart Protect

Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Provide ventilation for receptacles.

- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: 0°C to +35°C

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

CAS: 1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

CAS: 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

· Ingredients with biological limit values:

CAS: 1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

(Contd. on page 5)



Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 4)

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Do not breathe spray.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Wear respiratory protection.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

PVA aloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Viscous

Colour: According to product specification

· Odour: Characteristic

· pH-value:

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 137-143 °C

51 °C · Flash point:

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

Density at 20 °C: 0.98 g/cm³

· Solubility in / Miscibility with

water: Immiscible / difficult to mix.

· Solvent content:

VOC (EU) 112.0 g/l VOC (EC) 112 g/l 11.18 %

 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

(Contd. on page 7)



Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 6)

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Methanol

Nitrogen oxides

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	alues rele	evant for classification:
CAS: 133	0-20-7 xyle	ene (mix)
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	27.124 mg/L (rat)
	LC50/4 h	5,000 ppmV (rat)
CAS: 1382	22-56-5 3-((trimethoxysilyl)propylamine
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>10,000 mg/kg (rabbit) (OECD 402)
CAS: 100-	41-4 ethyl	benzene
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: Repeated exposure may cause skin dryness or cracking.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Smart Protection

Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	xicity:
CAS: 1330	-20-7 xylene (mix)
LC50/96 h	4.2 mg/L (rainbow trout)
EC50/48 h	2.93-4.4 mg/L (daphnia magna)
CAS: 1382	2-56-5 3-(trimethoxysilyl)propylamine
LC50/96 h	>934 mg/L (brachydanio rerio) (OECD TG 203)
EC50/48 h	331 mg/L (daphnia magna) (OECD TG 202)
EC50/72 h	>1,000 mg/L (desmodesmus subspicatus) (OECD 201)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:

CAS: 1330-20-7 xylene (mix)

IC50/72 h 2.2 mg/L (algae)

- · Additional ecological information:
- · General notes:

Overall evaluation

Avoid transfer into the environment.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

· European	waste catalogue
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 9)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Smart Protection

Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 8)

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Non contaminated packagings may be recycled.

SECTION 14: Transport information	on	
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name		
ADR	Void	
	Void	
· ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR	2.2.3.1.1 (note 1)	
· IMDG	2.3.1.3	
·IATA	3.3.1.3	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) STATUTORY INSTRUMENTS 2012 No. 1715 ENVIRONMENTAL PROTECTION | The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012, and any subsequent amendments

(Contd. on page 10)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Smart Protection

Printing date 11.06.2021 Version number 9 Revision: 11.06.2021

Trade name: Nullifire SC902 B

(Contd. of page 9)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.