

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: illbruck FM320

· MSDS code: A-I-FM320

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Tremco CPG Netherlands B.V. Vlietskade 1032, 4241 WC Arkel T: +31 (0) 183568000, F: +31 (0) 183568100 msds@cpg-europe.com

· Further information obtainable from:

Tremco CPG UK Ltd Coupland Road, Hindley Green, Wigan, WN2 4HT T: +44 (0) 1942251400, F: +44 (0) 1942251410 www.cpg-europe.com, info.uk@cpg-europe.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.	
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Contains:

diphenylmethanediisocyanate, isomers and homologues

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P284 In case of inadequate ventilation wear respiratory protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Active substance with propellant

· Dangerous components:	
CAS: 9016-87-9 EC number: 618-498-9 diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30-<50%

(Contd. on page 3)



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

	(Co	ntd. of page 2)
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	-
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 115-10-6	dimethyl ether	5-<10%
EINECS: 204-065-8	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	-
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 74-98-6	propane	5-<10%
EINECS: 200-827-9	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	-
Reg.nr.: 01-2119486944-21-xxxx	,	
CAS: 1244733-77-4	tris(2-chloro-1-methylethyl)phosphate	1-<5%
EC number: 807-935-0	Acute Tox. 4, H302	-
Reg.nr.: 01-2119486772-26-xxxx		

· SVHC -

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2)

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

If symptoms persist consult doctor.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Immediately remove all soiled and contaminated clothing

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Nausea

- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

illbruck

Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 3)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

Formation of toxic gases is possible during heating or in case of fire.

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

- 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)



Safety data sheet (EC) No 1907/2006, as amonded by UK SI 2019/7

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from water.
- Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingre	Ingredients with limit values that require monitoring at the workplace:		
CAS:	9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO		
CAS:	CAS: 115-10-6 dimethyl ether		
	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm		
· PNEC	S		
CAS:	9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
PNEC	1 mg/L (fresh water)		
	10 mg/L (intermittent release)		
	0.1 mg/L (salt water)		
CAS:	115-10-6 dimethyl ether		

PNEC 0.155 mg/L (fresh water)

160 mg/L (sewage treatment plant)

1.549 mg/L (intermittent release)

0.016 mg/L (salt water)

PNEC 0.045 mg/kg (soil)

0.069 mg/kg (sediment (salt water))

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

PNEC 0.64 mg/L (fresh water)

0.064 mg/L (marine)

(Contd. on page 6)



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 5)

PNEC 1.7 mg/kg dwt (soil)

1.34 mg/kg dwt (sediment (salt water))

- Additional Occupational Exposure Limit Values for possible hazards during processing:
- Carbon dioxide (CO2)
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

Eye protection:



Tightly sealed goggles

(Contd. on page 7)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 6)

· Body protection:



Protective work clothing

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

pH-value: Mixture is non-polar/aprotic.Melting point/freezing point: Not applicable, as aerosol.

Undetermined.

· Flash point: -97 °C

• Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

• **Decomposition temperature:** Not determined.

Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 1.7 Vol % **Upper:** 18.6 Vol %

· Vapour pressure at 20 °C: <1.1 hPa

Density at 20 °C: 0.94 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Immiscible / difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 8)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

		(Contd. of page 7)
Kinematic:	Not determined.	
· Solvent content:		
VOC (EU)	201.8 g/l	
VOC (EC)	21.47 %	
• 9.2 Other information No further relevant information available.		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity

Harmful if inhaled

Hammun	Harmiui ii iiinaleu.		
· LD/LC50	· LD/LC50 values relevant for classification:		
CAS: 901	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
Oral	LD50	>10,000 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.5 mg/L (rat)	
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate			
Oral	LD50	632 mg/kg (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

(Contd. on page 9)



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 8)

- · **Reproductive toxicity** Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 9016	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
LC0/96 h	>1,000 mg/L (brachydanio rerio)		
EC50/24 h	>1,000 mg/L (daphnia magna)		
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate			
LC50/96 h	LC50/96 h 51 mg/L (pimephales promelas)		

- · 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is not easily biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d > 10 mg/L (daphnia magna)

Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
08 05 01*	waste isocyanates	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
-	(Contd. on page 10)	

(Contd. on page 10)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

	(Contd. of page 9)
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising
	•

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADD IMDG IATA	

· **ADR, IMDG, IATA** UN1950

· 14.2 UN proper shipping name

· **ADR** 1950 AEROSOLS 1950 AEROSOLS

· IMDG AEROSOLS

AEROSOLS, flammable, containing substances in

Division 6.1, Packing Group III

- · 14.3 Transport hazard class(es)
- · ADR





• Class 2 5TF Gases. • Label 2.1+6.1

· IMDG





· Class 2.1 · Label 2.1/6.1

·IATA





· Class 2.1 · Label 2.1 (6.1)

(Contd. on page 11)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

	(Contd. of page 1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacit above 1 litre: Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II Marpol and the IBC Code	of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	120 ml Code: E0 Not permitted as Excepted Quantity 1 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1 (6.1)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "EU-CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1)

(Contd. on page 12)



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

(Contd. of page 11)

"EU-REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments) COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.

75/324/EEC relating to aerosol dispensers

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) "GB-CLP" The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK-REACH" The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eve irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 13)



(Contd. of page 12)

Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 17.09.2021 Version number 4 Revision: 17.09.2021

Trade name: illbruck FM320

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* * Data compared to the previous version altered.

GB